

FBA Series

Chip Ferrite Bead SMD Type
Size 0805




FEATURES

- E} • } μ } v • } o μ } v (} } P v } o • } P v o
- s } } μ • (} } < μ v } } Z } } } } } • } • Á } } Z } } u } } + } } v } } (} } } μ } } • (} } } } μ v } } } } } • μ } • } } } } Z } } v P (} } } u } } P v } } o • } } P v o • } } } } Z } } P Z r • %
- r Y } } } } } < μ o } }.
- K % } } } } v P } } u % } } } } μ } } W r } } } } } } } } = } } } } } }
-


APPLICATION

-

Dimensions: [mm]



Land Pattern: [mm]





Electrical Properties:

	Impedance @ 100MHz (Ω)	DC Resistance Max. (Ω)	Temperature Rise Current Max. (mA)
& } } } } } } } } } } } }	íí	%	
& } } } } } } } } } } } }	íó	%	
& } } } } } } } } } } } }	îò	%	
& } } } } } } } } } } } }	ïì	%	
& } } } } } } } } } } } }	ðì	%	
& } } } } } } } } } } } }	òì	%	
& } } } } } } } } } } } }	íî	%	
& } } } } } } } } } } } }	íñ	%	
& } } } } } } } } } } } }	îî	%	
& } } } } } } } } } } } }	ïì	%	
& } } } } } } } } } } } }	ðó	%	
& } } } } } } } } } } } }	òì	%	
& } } } } } } } } } } } }	íì	%	
& } } } } } } } } } } } }	íì	%	
& } } } } } } } } } } } }	íñ	%	
& } } } } } } } } } } } }	îì	%	
& } } } } } } } } } } } }	îì	%	



Typical Electrical Characteristics:




Soldering Reflow:




Packaging Information:

Tape Dimension :




Series	A0 (mm)	B0 (mm)	D (mm)	P0 (mm)	P1 (mm)	W (mm)	K0 (mm)	E (mm)	T (mm)
0805	1.30±0.05	2.10±0.05	1.5±0.1	4.0±0.1	4.0±0.1	8.0±0.3	0.95±0.05	1.75±0.1	0.95±0.05

Peel force of top cover tape:



The peel force of top cover tape shall be between 0.14 to 0.58 N

Reel Dimension: [mm]



Cautions and Warnings:

Storage Conditions:

- The storage period is within 12 months after the completion of production. Be sure to follow the storage conditions (temperature: -5 to 35°C, humidity: 75% RH Max). If the storage period elapses, the soldering of the terminal electrodes may deteriorate. The warranty period is one year.
- Product should not be exposed to environment with high temperature, high humidity, dust, corrosive gas and etc.
- Products should be handled with care to avoid damage or contamination from perspiration and skin oils.
- Please always handle products carefully to prevent any damage caused by dropping down or inappropriate removing.

Operation Instructions:

- Self heating (temperature increase) occurs when the power is turned ON, so the tolerance should be sufficient for the set thermal design.
- Before soldering, be sure to preheat components. The preheating temperature should be set so that the temperature difference between the solder temperature and chip temperature does not exceed 150°C.
- Soldering corrections after mounting should be within the range of the conditions determined in the specifications. If overheated, a short circuit, performance deterioration, or lifespan shortening may occur.
- Generally, Koher might not be familiar with either customer's specific application or actual requests as customer does. As a result customer shall be responsible for checking and confirming whether Koher product with the performance described in the product specification is suitable for using in customer's particular application or not.