



- ,
-
-
- ! tÚWf- f2Ø òdzlî y2laS řdzS ú2 Y2třlyY Ō2yaúWdzŌæzy
-
- hLjSñWf-əyÉ úSYLjSñWf-údzNŠ Wf-yÉS π pp c / ú2 Ъ mnp c /
- vdzl-yəúèY уллLJŌä

☐ ☐ ☐ ☐ ☐

The diagram illustrates the layout of a page. The total width is 9.5 typ. and the total height is 5.5 typ. A shaded rectangular area is positioned on the left, and a white rectangular area is on the right. The width of the white area is 4.0 typ.

Part No	Inductance @ 100kHz/1V (μH)	Tolerance	DC Resistance Max. (mΩ)	Satura on Current Max. (A)	Temperature Rise Current Max. (A)
а 59луплпнн а			мфл		
а 59луплпвоо а					
а 59луплпвт а	лфт				
а 59луплпврс а					
а 59луплпвсу а					нмфл
а 59луплпвун а				мфл	мфл
а 59луплпмвл а	мфл			мтфл	мтфл
а 59луплпмвра а	мфрл		тфсл	мрфл	мрфл
а 59луплпмву а	мфл		ммфл	мофр	мнфр
а 59луплпнн а			ммфп	мнфл	мнфл
а 59луплпвоо а			мрфл	ммфл	млфл
а 59луплпвт а	пфтл			млфр	
а 59луплпврс а				млфл	
а 59луплпвсу а					тфл
а 59луплпун а				тфтл	
а 59луплпмл а	млфл			тфл	

Part No	Inductance @ 100kHz/1V (μ H)	Tolerance	DC Resistance Max. (m Ω)	Satura on Current Max. (A)	Temperature Rise Current Max. (A)
а 59луплпмрл а	мрџл		тмџл		
а 59луплпннл а			ммо		
а 59луплпоол а			мрс		
а 59луплптл а	птџл				

Saturation Current will cause L to drop approximately 30%

Temperature Rise Current: The actual value of DC current when the temperature rise is $\Delta T=40^{\circ}\text{C}$