

Molding SMD Power Inductors

- Low profile and low DCR.
 - Magnetically Shielded construction, low EMI.
 - Frequency range up to 5MHz.
 - High power efficiency.
 - High current carrying capacity, Low core loss.
- Operating temperature: -55 to +125 °C

Dimensions: [mm]

MDPA0440	4.1±0.25	4.1±0.25	4.1 max	3.4	±0.3	1.2	
MDPA0550	5.5±0.30	5.3±0.30	5.0 max	4.3±0.3	1.10±0.3	2.0	4.5
MDPA0660			6.1 max	5.3	1.40±0.3	2.5	5.6

Electrical Properties:

MDPA0440-2R2M	2.20	±20%			15.0


MDPA0550-100M	10.0	±20%	6.2	5.5	33.0

MDPA0660-220M	22.0	±20%	5.4		52.0

Saturation Current will cause L0 to drop approximately 30%.

Temperature Rise Current: The actual value of DC current when the temperature rise is $\Delta T=40\text{ }^{\circ}\text{C}$.

Soldering Reflow:



Packaging Information:

Tape Dimension: [mm]

Series	D typ.	P0 typ.	P1 typ.	W typ.	E typ.
	1.5			12.0	1.75
0550	1.5		12.0	16.0	1.75
	1.5		12.0	16.0	1.75

Product Marking:

Marking	Printing (Inductance)
---------	-----------------------

Reel Dimension: [mm]

